



Microline Dot Matrix Printer

ML184 Turbo + 9-Pin Dot Matrix Printer

The reliable and affordable printer for industrial and point of sale applications

As the entry level printer in our 9-pin dot matrix range, the ML184 Turbo is fast and robust, yet compact and light. A true demand document printer with bottom feed and short tear, its special size makes it ideal for customer service environments and industrial workstation applications.

Highlights:

- Compact 80 column dot matrix printer
- OKI Printing Solutions unique, high durability 9-pin print head
- Multi-part continuous forms handling (original + 3 copies)
- Up to 375 characters per second print speed
- Ideal for data logging, label printing and point of sale use
- Suited to harsh environments
- DC version also available for remote or mobile use



ML184 Turbo +

		ML184 Turbo+	ML184 Turbo+ (DC)
General	Number of pins	9	
	No. of multi-part forms	4 (one original + 3 copies)	
Speed and throughput	Super speed draft (12cpi only)	375cps	300cps
	High speed draft (all cpi)	333cps	240cps
	Utility (all cpi)	250cps	200cps
	Near letter quality (all cpi)	62.5cps	50cps
	Fastest print speed	375cps	300cps
Font & print features	Carriage width (10cpi)	80 columns	
	Max. in compression mode	160 columns	
	Character pitch	10/12/15/17.1/20 pitch & proportional	
	Graphics resolution	Up to 240 x 216 dpi	
	Typeface & Font	Utility, High Speed Draft, NLQ, Barcodes	
Emulations & Interfaces	Printer emulations	Epson LX, IBM Graphics or Oki MicroLine	
	Standard interfaces	Centronics Parallel, USB	
	Optional interfaces	Serial RS 232C/RS 422/Current Loop	
Paper handling	Continuous paper	76.2 – 241.3mm	
	First printable line (from top of page)	Cut sheet: 15mm, Continuous: 16.9mm	
	Standard	Autoload single sheet, Platen pin feed, Low tear-off, Paper end detection	
	Optional	Roll paper stand, Pull tractor feed, Single bin sheet feeder	
Physical	Dimensions (HxWxD)	80 x 372 x 275mm	
	Weight	4.5kg	4.0kg
	Memory	128KB	
	Noise level	51dB (quiet mode)	
Power	Power requirements	220V-240V AC	9.6 – 31.2V DC
	Frequency	50/60Hz	
Reliability	Print head life	200 million characters	
	Ribbon life	3 million characters (re-inking cartridge)	
	MTBF	20,000 hours	

Consumables Information: Only use genuine OKI Printing Solutions Original consumables to ensure the best quality and performance from your hardware. Non OKI Printing Solutions Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.

OKI DATA CORPORATION.
4-11-22 Shibaura, Minato-Ku
Tokyo 108-8551 Japan
Tel: (81) 3 5445 6452
Fax: (81) 3 5445 6456
WWW.OKIDATA.CO.JP

OKI DATA (SINGAPORE) PTE LTD.
78 Shenton Way #09-01
Lippo Centre
Singapore 079120
Tel: (65) 6221 3722
Fax: (65) 6421 1688
WWW.OKI.COM.SG

OKI DATA (SINGAPORE) PTE LTD.
Malaysia Rep. Office
Suite 21.03, 21st Floor
Menara IGB, Mid Valley City
59200 Kuala Lumpur, Malaysia
Tel: (03) 2287 1177
: 1800 88 1177 (Toll Free)
Fax: (03) 2287 1166
WWW.OKI.COM.MY

OKI SYSTEMS (THAILAND) LTD.
1168/81-82 Lumpini Tower,
27th Floor Rama IV Road,
Tungmahamek, Sathorn
Bangkok 10120
Tel: (662) 679 9235
Fax: (662) 679 9243/245
WWW.OKISYSTHAI.COM



As an ENERGY STAR Partner, Oki has determined that this product meets the ENERGY STAR guidelines for energy efficiency.

OKI
PRINTING SOLUTIONS