



Microline Dot Matrix Printers

ML320 Turbo ML321 Turbo 9-Pin Dot Matrix Printer

High performance, versatile printer for dedicated forms printing

The ML320 Turbo/ML321 Turbo narrow and wide carriage printers are suited to high speed, high volume data and word processing applications where fast throughput and flexible paper management are required. Outstanding reliability, ease-of-use and barcoding facilities make them ideal for customer service points in wholesale, retail and service environments that produce applications.

Highlights:

- 80/136 column dot matrix printers
- High durability 9-pin print head
- Up to 435 characters per second print speed
- Multi-part paper-handling (original + 4 copies)
- Wide carriage (ML321 Turbo) ideal for accounts applications



ML320 Turbo/ML321 Turbo

| | | ML320 Turbo | ML321 Turbo |
|------------------------------------|---|---|-------------------|
| General | Number of pins | 9 | |
| | No. of multi-part forms | 5 (one original + 4 copies) | |
| Speed and throughput | Super speed (12cpj) | 435cps | |
| | High speed draft (12cpj & 10cpj) | 387cps | |
| | Utility (12cpj & 10cpj) | 290cps | |
| | Near letter quality (12cpj & 10cpj) | 73cps | |
| | Fastest print speed | 435cps | |
| Font & print features | Carriage width (10cpj) | 80 columns | 136 columns |
| | Max. in compression mode | 160 columns | 272 columns |
| | Character pitch | 10/12/15/17.1/20 pitch & proportional | |
| | Graphics resolution | Up to 240 x 216 dpi | |
| | Typeface & Font | NLQ-Courier (Scalable), NLQ-Gothic (Scalable), OCR-B, High Speed Draft, Utility + Barcodes | |
| Emulations & Interfaces | Printer emulations | Epson FX, IBM ProPrinter/Graphics, Oki MicroLine | |
| | Standard interfaces | Centronics Parallel + USB | |
| | Optional interfaces | Serial RS 232C/RS 422/Current Loop | |
| Paper handling | Continuous paper | 76–254mm | 76–406mm |
| | Continuous envelopes | 165 x 91mm | 239 x 102mm |
| | First printable line (from top of page) | 8.9mm | |
| | Standard | Paper parking, Zero tear-off, Autoload single sheet, Push tractors, Bottom feed | |
| | Optional | Pull tractors, Single/dual bin cut-sheet feeder, Roll paper stand (ML320 Turbo only), Bottom tractors with metal long-life tear-off bar | |
| Physical | Dimensions (HxWxD) | 116 x 398 x 345mm | 116 x 552 x 345mm |
| | Weight | 6.5kg | 8.5kg |
| | Memory | 88KB | |
| | Noise level | 57dB(A)/52dB(A) (quiet mode) | |
| Power | Power requirements | 230V AC | |
| | Frequency | 50/60Hz | |
| Reliability | Print head life | 200 million characters | |
| | Ribbon life | 3 million characters in utility mode at 10cpj (re-inking cartridge) | |
| | MTBF | 10,000 hours | |

Consumables Information: Only use genuine OKI Printing Solutions Original consumables to ensure the best quality and performance from your hardware. Non OKI Printing Solutions Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.

OKI DATA CORPORATION.

4-11-22 Shibaura, Minato-Ku
Tokyo 108-8551 Japan
Tel: (81) 3 5445 6452
Fax: (81) 3 5445 6456
WWW.OKIDATA.CO.JP

OKI DATA (SINGAPORE) PTE LTD.

78 Shenton Way #09-01
Lippo Centre
Singapore 079120
Tel: (65) 6221 3722
Fax: (65) 6421 1688
WWW.OKI.COM.SG

OKI DATA (SINGAPORE) PTE LTD.

Malaysia Rep. Office
Suite 21.03, 21st Floor
Menara IGB, Mid Valley City
59200 Kuala Lumpur, Malaysia
Tel: (03) 2287 1177
: 1800 88 1177 (Toll Free)
Fax: (03) 2287 1166
WWW.OKI.COM.MY

OKI SYSTEMS (THAILAND) LTD.

1168/81-82 Lumpini Tower,
27th Floor Rama IV Road,
Tungmahamek, Sathorn
Bangkok 10120
Tel: (662) 679 9235
Fax: (662) 679 9243/245
WWW.OKISYSTHAI.COM



As an ENERGY STAR Partner, Oki has determined that this product meets the ENERGY STAR guidelines for energy efficiency.

OKI
PRINTING SOLUTIONS