

OKI



ML5790

\$669 (rrp)

Key specifications

Print speed:High Speed Draft: 576cps (12cpi); High Speed Draft: 480cps (10cpi); Draft: 540cps (15cpi); Draft: 432cps (12cpi); Draft:360cps (10/20cpi); Draft: 309cps (17.1cpi); Letter Quality:240cps (20cpi); Letter Quality: 206cps (17.1cpi); Letter Quality:180cps (15cpi); Letter Quality: 144cps (12cpi); Letter Quality:120cps (10cpi)

Number of copies:Up to 1 original + 5 copies (Pull tractor); Up to 1 original + 6 (Push tractor)

Full specifications

24

80 (10cpi); 160 (maximum in compression mode)

HSD, Draft, Courier (scalable), Roman (scalable), Swiss (scalable), Swiss Bold, Orator, Gothic, Prestige, OCR-A, OCR-B

Emphasised, Enhanced, Double Width, Double Height, Italics, Outline, Shadow, Superscript, Subscript, Underline

Windows 2000 / XP (32-bit & 64-bit) / Vista (32-bit & 64-bit) / 7 (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) /Server 2008 (32-bit & 64-bit) / Server 2008 R2 (64-bit)

Status monitor, Button setup utility, Menu setup utility, TOF setup utility

Cut Sheet (single sheet), Continuous Paper (single-part, multi-part), Roll paper, Envelope, Card, Label (cut sheet and fan fold)

Width: ML5790eco: 76.2 - 254.0mm / Length: 76.2 - 558.8mm

Continuous: 2.12mm; Cut sheet: 0.5mm

Front/rear push feed: 0.36mm; Front/rear pull feed & front/rear push-pull feed: 0.44mm; Bottom pull feed: 0.48mm

128Kbytes

Single phase 220 to 240VAC, +/- 10%

ISO/IEC 10561 Letter, Draft, Range1: 88W; Sleep mode (no options attached): 1.5W

Normal: 57dB(A); Quiet: 52dB(A); Silent mode: 49dB(A)

191 x 438 x 375mm

7.5kg approx

This product complies with EN55022 Class B. However when fitted with the optional network interface card or optional cut sheet feeder, compliance to EN55022 is Class A. In a domestic environment this configuration may cause radio interference, in which case the user may be required to take adequate control measures.

Printing Characteristics

Character pitch:5/6/7.5/8.5/10/12/15/17.1/20 pitch and proportional

Print speed:High Speed Draft: 576cps (12cpi); High Speed Draft: 480cps (10cpi); Draft: 540cps (15cpi); Draft: 432cps (12cpi); Draft:360cps (10/20cpi); Draft: 309cps (17.1cpi); Letter Quality:240cps (20cpi); Letter Quality: 206cps (17.1cpi); Letter Quality:180cps (15cpi); Letter Quality: 144cps (12cpi); Letter Quality:120cps (10cpi)

Built in barcodes:UPC-A, UPC-E, EAN8, EAN13, Code39, Interleaved 2of5, Code128 (A/B/C), CODABAR (NW-7), POSTNET, Industrial 2of5, Matrix 2of5,

Interfaces and Emulations

Interface:IEEE 1824 parallel interface, USB 2.0 (full speed)

Optional interface(s):Ethernet 10/100, Serial RS232C

Emulation:Epson LQ ESC/P2, IBM PPR, IBM AGM

Paper Handling

Number of copies:Up to 1 original + 5 copies (Pull tractor); Up to 1 original + 6 (Push tractor)

Standard paper handling:Manual insertion: Front or rear in, top out; Push Tractor: Front or rear in, top out; Pull tractor: Front or rear or bottom in, top out

Optional paper handling:Single Bin Cut Sheet Feeder, Push Tractor (front/rear feeds), Pull Tractor (bottom feed), Roll Paper Stand

Reliability

Print head life:400 million characters

Reliability:MTBF: 25,000 hours

Other Specifications

Warranty:1 year standard warranty, onsite next business day

Oki Data (S) Pte Ltd - 438A Alexandra Road #02-11/12, Lift Lobby 3, Alexandra Technopark,

Singapore 119967, Tel: +65 6221 3722 e-mail:odsp-sales@oki.com