

OKI



B720

\$1199 (rrp)

Full specifications

45ppm

8 seconds

Up to 38 seconds from power on & up to 25 seconds from power save

600MHz

IEEE1284 Bi-directional parallel, Hi-Speed USB 2.0, 10/100BaseTX Ethernet, RS-232C Serial, Host USB Port for direct printing of PDF

PCL6, PCL5e, Adobe® PostScript 3, SIDM (Epson FX), Direct PDF printing

10/100Base TX Ethernet card with internal web server for printer and network card set-up and management. Includes SMTP mail client for alerts. All major network protocols supported: TCP/IP : IPv4, IPv6, ICMP, ARP, RARP, DHCP/BOOTP, "Port 9100", LPR/LPD, Apple Bonjour (mDNS), Dynamic DNS, DNS/WINS, HTTP, SMTP, POP3, FTP, SNMPv1/v2/v3, Ethertalk, Netware IPX/SPX, Network Security Protocols : IPsec, 802.1x
Wired Authentication: EAP-MD5, PEAP, EAP-TLS

Windows 2000 / XP Home / XP Professional (32-bit & 64-bit) / Vista (32-bit & 64-bit) / 7 (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit); Mac OS X 10.2 - 10.6

Template Manager, PrintSuperVision, OKI LPR, PDF Print Direct, Secure Print, Storage Device Manager, Status Monitor

PCL: 99 scalable PCL and 1 bitmap font; PostScript 3: Adobe Standard 136

Epson FX

11 types of one dimension with 28 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4POSTNET

Tray 3: 550 sheets of 80gsm; Tray 4: 550 sheets of 80gsm

1,800 sheets of 80gsm

Tray 1/2/3/4: 64 to 216gsm; Duplex: 64 to 216gsm

Standard: B720dn; Optional: B720n

Standard: 128MB; Maximum: 640MB

Standard: 40MB on board for storage of fonts, form and macros; Optional: 1GB

5°C to 35°C/ 15% to 85% RH non-condensing

0°C to 35°C/ 15% to 80% RH non-condensing

230VAC +/- 10%, 50 or 60Hz +/- 2%

Typical: 904W; Max: 1200W; Standby: 169W; Power Save: 10.3W

Operating: 64dB(A) or less; Standby: 30dB(A) or less; Power save: Background level (including all available options)

B720n: 404 x 422 x 465mm; B720dn: 404 x 422 x 572mm

B720n: 21.1kg; B720dn: 23.2kg

200,000 pages/month

5,000 - 17,500 pages/month

1 year standard warranty

Print quality

Resolution600 x 600dpi, 1200 x 1200dpi

Paper Handling

Paper capacityTray 1: 150 sheets of 80gsm; Tray 2: 550 sheets of 80gsm

Paper sizesTray 1: A4, A5, A6, B5, Letter, Legal 13 & 14, Oficio, Executive, Statement, Banner size: 210 x 900, 210 x 1200, Custom size: Width 76-215mm Length 127-1219mm, Envelopes: Com-9, Com-10, DL, C5, Monarch; Tray 2/3/4: A4, A5, A6, B5, Letter, Legal 13 & 14, Oficio, Executive, Statement, Custom size: Width 98-215mm Length 148-355mm, Envelopes: Com-9, Com-10, DL, Monarch; Duplex: A4, A5, A6, B5, Letter, Legal 13 & 14, Executive, Statement, Custom size: Width 88-215mm Length 139-355mm

Paper outputFace down: 500 sheets of 80gsm; Face up: 70 sheets of 80gsm; Optional Offset catch tray: 500 sheets of 80gsm

Oki Data (S) Pte Ltd - 438A Alexandra Road #02-11/12, Lift Lobby 3, Alexandra Technopark,

Singapore 119967, Tel: +65 6221 3722 e-mail:odsp-sales@oki.com